

# Single-Bay Desktop Battery Charger



For Harris  
XL200 Radios



\*radio and battery not included

## PRODUCT FEATURES:

- Fast charging Harris battery.
- Charge at current rates recommended by the battery manufacturer.
- Be suitable to operate at the office (With AC power supply) as well as in the vehicle DC (with proper cabling).
- Switch to a maintenance mode once the battery is fully charged. Charger will monitor battery voltage in order to keep its full capacity without ever overcharging or overheating.
- Mounting holder for mobile application is available

## PRODUCT SPECIFICATIONS:

- Dimensions: 6.25" x 3.75" x 2.75"
- Weight: 1 lb.  $\pm$ 5%
- Operating temperature: -20°C to +50°C
- Storage temperature: -40° C to +85°C
- Relative humidity: 95% maximum none condensing
- Power supply:  
Input: 115VAC-230 VAC, OUTPUT: 15VDC 800mA  
Cord: 6 ft 22 AWG x 2C, 90C
- Charger Input: 2.5 mm center positive: 12VDC-24VDC  $\pm$ 20% , 800mA
- Switching charging circuit: on board to minimize heat generation
- Charging system (each charging bay ): 800mA ,4.2 VDC  $\pm$  0.3%

INNOVATIVE ENGINEERING AND MANUFACTURING FOR OVER 25 YEARS

305-623-3939 | 1-800-881-8211 | jlopez@advancetec.com | www.AdvanceTec.com